


Part No: 2201POFPL-E00
Description: 1 x 2 x 22(7)AWG Single Pair Foil Screened LSF Data Cable.



Construction

Conductor Material	: Tinned Copper, 22(7)awg
Pair Insulation Material	: Polyethylene (PE)
Number of Pairs	: 1
Overall Screen	: Aluminium Foil (100% Coverage)
Drain Wire	: Tinned Copper, 22(7)awg
Sheath Material	: Low Smoke and Fume (LSF)
Sheath Colour	: Grey
Core Identification	: Clear/Black
Alternative to Belden	: 8761

Electrical Characteristics

Nominal Conductor Resistance @20°C	: < 55.2 Ω/km
Capacitance	Core to core : 65 pF/m ± 25
	Core to screen : 122 pF/m ± 35
Impedance	: 85 Ω ± 25
Voltage Rating	: 450/750 V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5 kV for 5 minutes

Physical Characteristics

Overall Diameter	: 4.5 ± 0.2mm
Min. Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 25 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)