

**Part No:** 2201PUGH-E00  
**Description:** 1 x 2 x 22(1)AWG Unscreened Paired Low Smoke Halogen Free (LSHF) Data Cable White



### Construction

Conductor Material : Tinned Copper, 22(1)awg  
 Insulation Material : Polyethylene (PE)  
 Number of Pairs : 1  
 Sheath Material : Low Smoke Halogen Free (LSHF)  
 Sheath Colour : White  
 Core Identification : White/Blue Stripe, Blue/White Stripe  
 Alternative to Belden : 7701NH

### Electrical Characteristics

Nominal Conductor Resistance : < 57.8 Ω/km  
 Capacitance Core to core : 46 pF/m ± 15  
 Impedance : 100 Ω ± 10  
 Voltage Rating : 450/750 V *Applies to CE marked FSC branded stock only*  
 Test Voltage : 2.5 kV for 5 minutes

### Physical Characteristics

Overall Diameter : 3.5 ± 0.2mm  
 Min. Bend Radius : 10 x OD  
 Temperature Rating : -20°C to +70°C  
 Weight : 14 kg/km

### Standards

Flame Retardant : BS EN 60332-1-2  
 Low Smoke Generation : BS EN 61034-2  
 Halogen Gas Emission : BS EN 60754-1&2  
 RoHS3 Compliant : Yes  
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)  
 CPR Classification : Eca (EN50575:2014+A1:2016)