

**Part Number:** 2403POFYD-L00  
**Description:** 3 x 2 x 24(7)AWG Three Pair Foil Screened External Duct Grade Data Cable



### Construction

Conductor Material	: Tinned Copper, 24(7)awg
Insulation Material	: Low Smoke & Fume (LSF)
Number of Pairs	: 3
Overall Screen	: Aluminium Foil (100% Coverage)
Drain Wire	: Tinned Copper, 24(7)awg
Inner Sheath Material	: Low Smoke & Fume (LSF)
Inner Sheath Colour	: Grey
Outer Sheath Material	: Polyethylene (PE)
Outer Sheath Colour	: Black
Core Identification	: Black/Red, Black/White, Black/Green
Alternative to Belden	: 9503, Duct Grade

### Electrical Characteristics

Nominal Conductor Resistance	: < 86.2 $\Omega$ /km
Insulation Resistance	: > 200M $\Omega$ .M
Capacitance	Core to Core : 98 pF/m $\pm$ 25
	Core to Screen : 164 pF/m $\pm$ 40
Voltage Rating	: 450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5kV for 5 minutes

### Physical Characteristics

Overall Diameter	: 8.3 $\pm$ 0.3mm
Min. Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 66 kg/km

### Standards

RoHS3 Compliant	: Yes
UV & Weather Resistant	: ISO 4892-3
CE Compliant	: LVD (2014/35/EU)
CPR Classification	: Fca (EN50575:2014+A1:2016)