


Part Number: 2404PODFL-E00
Description: 4 x 2 x 24(7)AWG Four Pair Foil & Braid Screened LSF Data Cable



Construction

Conductor Material	: Tinned Copper, 24(7)awg
Insulation Material	: Foamed Polyethylene (FPE)
Number of Pairs	: 4
Overall Screen 1	: Aluminium Foil (100% Coverage)
Drain Wire	: Tinned Copper, 24(7)awg
Overall Screen 2	: Tinned Copper Wire Braid (65% Coverage)
Outer Sheath Material	: Low Smoke & Fume (LSF)
Outer Sheath Colour	: Grey
Core Identification	: White/Blue Stripe, Blue/White Stripe White/Orange Stripe, Orange/White Stripe White/Green Stripe, Green/White Stripe White/Brown Stripe, Brown/White Stripe <i>(Please note the core identification may be supplied as banding)</i>
Alternative to Belden	: 8104

Electrical Characteristics

Nominal Conductor Resistance	: < 86.2 Ω/km
Insulation Resistance	: > 200MΩ.M
Impedance	: 100 Ohm ± 25
Capacitance	Core to Core : 41 pF/m ± 20 Core to Screen : 72 pF/m ± 35
Voltage Rating	: 450/750V <i>Applies to CE marked FSC branded stock only</i>
Test Voltage	: 2.5kV for 5 minutes

Physical Characteristics

Overall Diameter	: 7.7 ± 0.2mm
Min. Bend Radius	: 10 x OD
Temperature Rating	: -20°C to +70°C
Weight	: 80 kg/km

Standards

Flame Retardant	: BS EN 60332-1-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)