

Part Number: 2408COFYH-E00
Description: 8 x 24(7)AWG Eight Core Foil Screened Low Smoke Halogen Free (LSHF) Data Cable



Construction

| | |
|-----------------------|---|
| Conductor Material | : Tinned Copper, 24(7)awg |
| Insulation Material | : Low Smoke Halogen Free (LSHF) |
| Number of Cores | : 8 |
| Overall Screen | : Aluminium Foil (100% Coverage) |
| Drain Wire | : Tinned Copper, 24(7)awg |
| Outer Sheath Material | : Low Smoke Halogen Free (LSHF) |
| Outer Sheath Colour | : Grey |
| Core Identification | : Black, White, Red, Green, Brown, Blue, Orange, Yellow |
| Alternative to Belden | : 9538 |

Electrical Characteristics

| | |
|------------------------------|---|
| Nominal Conductor Resistance | : < 82.0 Ω/km |
| Insulation Resistance | : > 200MΩ.M |
| Capacitance | Core to Core : 108 pF/m ± 25 |
| | Core to Screen : 213 pF/m ± 40 |
| Voltage Rating | : 450/750V <i>Applies to CE marked FSC branded stock only</i> |
| Test Voltage | : 2.5kV for 5 minutes |

Physical Characteristics

| | |
|--------------------|------------------|
| Overall Diameter | : 5.7 ± 0.2mm |
| Min. Bend Radius | : 10 x OD |
| Temperature Rating | : -20°C to +70°C |
| Weight | : 49 kg/km |

Standards

| | |
|----------------------|------------------------------------|
| Flame Retardant | : BS EN 60332-1-2 |
| Low Smoke Generation | : BS EN 61034-2 |
| Halogen Gas Emission | : BS EN 60754-1&2 |
| RoHS3 Compliant | : Yes |
| CE Compliant | : LVD (2014/35/EU), CPR (305/2011) |
| CPR Classification | : Eca (EN50575:2014+A1:2016) |