

Part Number: 2410POFYL-E00
Description: 10 x 2 x 24(7)AWG Ten Pair Foil Screened LSF Data Cable



Construction

| | |
|-----------------------|--|
| Conductor Material | : Tinned Copper, 24(7)awg |
| Insulation Material | : Low Smoke & Fume (LSF) |
| Number of Pairs | : 10 |
| Overall Screen | : Aluminium Foil (100% Coverage) |
| Drain Wire | : Tinned Copper, 24(7)awg |
| Outer Sheath Material | : Low Smoke & Fume (LSF) |
| Outer Sheath Colour | : Grey |
| Core Identification | : Black/Red, Black/White, Black/Green, Black/Blue, Black/Yellow, Black/Brown, Black/Orange, Red/White, Red/Green, Red/Blue |
| Alternative to Belden | : 9510 |

Electrical Characteristics

| | |
|------------------------------|---|
| Nominal Conductor Resistance | : < 86.2 Ω/km |
| Insulation Resistance | : > 200MΩ.M |
| Capacitance | Core to Core : 98 pF/m ± 25 |
| | Core to Screen : 164 pF/m ± 40 |
| Voltage Rating | : 450/750V <i>Applies to CE marked FSC branded stock only</i> |
| Test Voltage | : 2.5kV for 5 minutes |

Physical Characteristics

| | |
|--------------------|------------------|
| Overall Diameter | : 9.5 ± 0.2mm |
| Min. Bend Radius | : 10 x OD |
| Temperature Rating | : -20°C to +70°C |
| Weight | : 119 kg/km |

Standards

| | |
|--------------------|------------------------------------|
| Flame Retardant | : BS EN 60332-1-2 |
| RoHS3 Compliant | : Yes |
| CE Compliant | : LVD (2014/35/EU), CPR (305/2011) |
| CPR Classification | : Eca (EN50575:2014+A1:2016) |