

Part No: 390179Y
Description: RG179 75 Ohm Coaxial Cable Foamed Polyethylene Insulation, Tinned Copper Braid, Polyvinyl Chloride (PVC) Black Sheath



Construction

Conductor Material : Solid Tinned Copper
 Stranding : 1/0.36mm
 Dielectric : Foamed Polyethylene (FPE)
 Diameter of Dielectric : 1.60mm (+/- 0.13mm)
 Screen Material : Tinned Copper Wire Braid (≥95% Coverage)
 Outer Sheath Material : Polyvinyl Chloride (PVC)
 Outer Sheath Colour : Black

Electrical Characteristics

Impedance : 75 Ω ± 8
 Capacitance : ≤ 57 pF /m ± 5
 Velocity of Propagation : 66 % ± 3
 Min Insulation Resistance @20°C : > 200 MΩ*M
 Max. Conductor Resistance @ 20°C : ≤ 197.1 Ω /km
 Voltage Rating : 30V

Attenuation @ 20°C

Frequency (MHz)	Attenuation (≤dB/100m)
10	16.1
100	33.4
200	45.5

Physical Characteristics

Overall Diameter : 2.65 ± 0.15mm
 Min. Bend Radius : 10 x OD
 Temperature Rating : -20°C to +70°C
 Weight : 12 kg/km

Standards

RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU)