


Part No: 390L40H75-E00
Description: ANT-400 75 Ohm Antennax Low Smoke Halogen Free (LSHF) Black Coaxial Cable



Construction

Conductor Material : Bare Copper
 Conductor Size : 1/1.65 mm
 Dielectric : Foam Polyethylene (FPE)
 Diameter of Dielectric : 7.24 mm
 1st Screen Material : Bonded Aluminium Foil
 2nd Screen Material : Tinned Copper Wire Braid (>86% Coverage)
 Outer Sheath Material : Low Smoke Halogen Free (LSHF)
 Outer Sheath Colour : Black



Electrical Characteristics

Impedance : 75 Ω ± 2
 Capacitance @ 1 kHz : 52.3 pF/m ± 5
 Velocity of Propagation : 85 %
 Conductor Resistance @ 20°C : ≤ 8.4 Ω /km
 Screen Resistance @ 20°C : ≤ 5.61 Ω /km
 Peak Power : 10.0 kW

Attenuation @ 20°C

Frequency (MHz)	Attenuation (dB/100ft)	Attenuation (dB/100m)	Frequency (MHz)	Attenuation (dB/100ft)	Attenuation (dB/100m)
30	0.64	2.3	1500	4.9	16.3
50	0.82	2.9	1800	5.4	18.0
150	1.5	4.8	2000	5.7	18.5
220	1.8	5.8	2500	6.4	21.5
450	2.6	8.5	5800	10.3	33.8
900	3.7	12.3			

Return Loss @ 20°C

Frequency (MHz)	Return Loss (dB)
30-2500MHz	≥ 15

Physical Characteristics

Overall Diameter : 10.3 mm (±0.20mm)
 Bending Radius : 5 x OD
 Temperature Rating : -40°C to +75°C
 Weight : 101 kg/km
 Flat Plate Crush : 0.71 kg/mm

Standards

Flame Retardant : BS EN 60332-1-2, BS EN 60332-3-24 Cat C
 Low Smoke Generation : BS EN 61034-2
 Halogen Gas Emission : BS EN 60754-1&2
 RoHS3 Compliant : Yes
 UV & Weather Resistant : ISO 4892-3
 CE Compliant : CPR (305/2011)
 CPR Classification : Eca (EN50575:2014+A1:2016)