



Nylon cable ties.

Key features.

- High quality self-extinguishing halogen free cable ties made from Nylon 6.6
- Available in black or natural
- Ideal for securing cables, pipes and hoses
- Used successfully in the most demanding industrial applications
- They can be quickly and easily installed either by hand or with one of our tensioning tools



Specification.

Material:
Nylon 6.6

Minimum installation temperature:
-10°C

Flammability rating:
UL 94 CLASS V2

Chemical resistance:
High resistance to bases, oils, greases, oil derivatives, chloride solvents; limited resistance to acids; not resistant to phenols.

UL file number: E509564



Part no. (Black)	Part no. (Natural)	Width (mm)	Length (mm)	Operating temperature range min / max (°C)		Min and max. bundle dia. (mm)	Loop tensile strength (N)	Pack quantity
				Black	Natural			
CTR 100-2.5B	CTR 100-2.5N	2.5	98	-40 / +85	-40 / +85	2 / 24	80	1000
CTR 160-2.5B	CTR 160-2.5N		160	-40 / +85	-40 / +85	2 / 42	80	1000
CTR 200-2.5B	CTR 200-2.5N		200	-40 / +85	-40 / +85	2 / 55	80	1000
CTR 140-3.6B	CTR 140-3.6N	3.5	140	-40 / +85	-40 / +85	2.5 / 36	150	1000
CTR 200-3.6B	CTR 200-3.6N		200	-40 / +85	-40 / +85	2.5 / 55	150	100
CTR 300-3.6B	CTR 300-3.6N		280	-40 / +85	-40 / +85	2.5 / 80	150	100
CTR 160-4.8B	CTR 160-4.8N	4.5	160	-40 / +85	-40 / +85	2.5 / 38	220	100
CTR 200-4.8B	CTR 200-4.8N		200	-40 / +85	-40 / +85	3 / 51	220	100
CTR 300-4.8B	CTR 300-4.8N		300	-40 / +85	-40 / +85	5 / 80	220	100
CTR 370-4.8B	CTR 370-4.8N	7.5	360	-40 / +85	-40 / +85	5 / 101	220	100
CTR 200-7.6B	CTR 200-7.6N		200	-40 / +85	-40 / +85	5 / 48	460	100
CTR 300-7.6B	CTR 300-7.6N		280	-40 / +85	-40 / +85	5 / 76	460	100
CTR 370-7.6B	CTR 370-7.6N	9.0	365	-40 / +85	-40 / +85	5 / 101	460	100
CTR 450-7.6B	CTR 450-7.6N		450	-40 / +85	-40 / +85	20 / 130	460	100
CTR 540-7.6B	CTR 540-7.6N		540	-40 / +85	-40 / +85	20 / 160	460	100
CTR 750-7.6B	CTR 750-7.6N	12.5	750	-40 / +85	-40 / +85	32 / 222	460	100
CTR 780-9.0B	CTR 780-9.0N		780	-40 / +85	-40 / +85	20 / 235	680	100
CTR 500HDB	Heavy duty only available in black		500	-40 / +85	-	10 / 140	980	50
CTR 720HDB		750	-40 / +85	-	40 / 222	980	50	
CTR 1000HDB		1000	-40 / +85	-	40 / 300	980	50	

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297

