



Pre-insulated nylon fork terminals.

Key features.

- Made from oxygen-free high conductivity copper
- Electro-tin plated for excellent conductivity and resistance to corrosion
- Create a secure and reliable, electrical and mechanical connection



Specification.

Material:
Electro-tin plated copper

Insulation:
Nylon

Max. electrical rating:
■ Red - 19 AMP
■ Blue - 27 AMP
■ Yellow - 48 AMP
 600 Volts - max.
 Max temperature 105° C

Approvals:
UL Approved E211389, RoHS compliant

Wire Ø mm ²	Part no.	Stud size D2 mm	Dimensions (mm)						Pack quantity
			B	L	F	E	D	D1	
0.5 - 1.5 Red	CNIF1-3	3.2	5.8	22.0	6.3	11.0	4.1	1.7	100
	CNIF1-3.5	3.7	5.8	22.0	6.3	11.0	4.1	1.7	100
	CNIF1-4	4.3	6.6	21.6	6.3	11.0	4.1	1.7	100
	CNIF1-5	5.3	8.0	22.0	7.0	11.0	4.1	1.7	100
	CNIF1-6	6.5	11.6	27.8	11.1	11.0	4.1	1.7	100
1.5 - 2.5 Blue	CNIF2-3	3.2	6.4	18.5	4.3	11.0	4.5	2.3	100
	CNIF2-3.5	3.7	6.4	18.5	4.3	11.0	4.5	2.3	100
	CNIF2-4	4.3	6.6	20.5	6.3	11.0	4.5	2.3	100
	CNIF2-5	5.3	8.5	23.0	7.8	11.0	4.5	2.3	100
	CNIF2-6	6.5	12.0	28.0	11.0	11.0	4.5	2.3	100
4-6 Yellow	CNIF3-3.5	3.7	7.2	22.5	5.9	13.0	6.5	3.4	50
	CNIF3-4	4.3	7.2	22.5	5.9	13.0	6.5	3.4	50
	CNIF3-5	5.3	9.5	26.0	8.3	13.0	6.5	3.4	50
	CNIF3-6	6.5	12.0	29.5	10.5	13.0	6.5	3.4	50
	CNIF3-8	8.4	15.0	34.2	13.7	13.0	6.5	3.4	50

01582 606033 | sales@cablecraft.co.uk | cablecraft.co.uk

Cablecraft House, Circle Business Centre, Blackburn Road, Houghton Regis, Bedfordshire, LU5 5DD

Registered in England and Wales at 12 Charterhouse Square, London EC1M 6AX | Company registration number 02478297

