



316 Stainless steel uncoated self-locking cable ties.

Key features.

- Manufactured from 316 stainless steel and have a high tensile strength
- The self-locking head design speeds installation and locks into place at any length along the tie
- The fully enclosed head does not allow dirt or grit to interfere with the locking mechanism
- These ties are flame retardant, tough and corrosion resistant
- London Underground Approved - Certificate No. 1732

Part number	Width (mm)	Length (mm)	Max. bundle dia. (mm)	Min tensile strength (Kg)	Pack quantity
CTR127ST	4.6	127	32	68	100
CTR150ST	4.6	150	43	68	100
CTR200ST	4.6	200	50	68	100
CTR300ST	4.6	300	76	68	100
CTR360ST	4.6	360	102	68	100
CTR520ST	4.6	520	152	68	100
CTR680ST	7.9	680	200	68	100
CTR200HDST	7.9	200	50	136	100
CTR300HDST	7.9	300	76	136	100
CTR360HDST	7.9	360	102	136	100
CTR520HDST	7.9	520	152	136	100
CTR680HDST	7.9	680	200	136	100
CTR840HDST	7.9	840	250	136	100
CTR1000HDST	7.9	1000	302	136	100
CTR360EHDST	12.7	360	110	317	100
CTR520EHDST	12.7	520	161	317	100
CTR620EHDST	12.7	620	192	317	100
CTR840EHDST	12.7	840	192	317	100
CTR1000EHDST	12.7	1000	313	317	100

Specification.

Material:
316 Stainless steel

Operating temperature:
-80°C to +538°C

Flammability:
Fireproof & UV resistant

Loop tensile strength:
4.6mm width: 667N (150lb), 7.9mm width: 1335N (300lb), 12.7mm width: 3115N (700lb)

Chemical resistance:
Salt spray resistant, corrosion resistant, weather resistant, outstanding chemical resistance, antimagnetic

Standards:
UL Cert. No: E227552, DNV Cert. No: E6729.
London Underground Approved Cert. No: 1732

