

Description: 7/0.2mm Def-Stan Multicore Type C Braid Screen, PVC Red Cable



Construction

Conductor Material : Tinned Copper, 7/0.2mm
 Conductor Insulation : Polyvinyl Chloride (PVC)
 Overall Tape : Polyester
 Overall Screen : Tinned Copper Braid
 Outer Sheath Material : Polyvinyl Chloride (PVC)
 Outer Sheath Colour : Red
 Core Identification :

1	Red	5	White
2	Blue	6	Black
3	Green	7	Brown
4	Yellow	8	Violet

Electrical Characteristics

Nominal Conductor Resistance @ 20°C : < 92 Ω/km
 Insulation Resistance : > 200 MΩ.M
 Voltage Rating : 440V rms up to 1600 MHz
 Test Voltage : 2.5kV for 5 Minutes
 Current Rating : 1 amps

Physical Characteristics

Overall Diameter : See Table
 Min. Bend Radius : 7.5 x OD
 Temperature Rating : -0°C to 70°C
 Weight : See Table

Standards

Flame Retardant : BS EN 60332-1-2
 RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU)
 Generally Manufactured to : Def Stan 61-12 Part 4

Part No.	Size	No. of Cores	Weight kg/km	O/D mm
3930020403	7-2-4C	4	33	4.6
3930020803	7-2-8C	8	66	6.4