Niltox® LF 318 Multicore H05Z1Z1-F White LSHF
Technical Datasheet

Description: Multicore Cable Low Smoke Halogen Free (LSHF) Throughout. Conforming to H05Z1Z1-F & Manufactured in accordance with EN 50525-3-11

NILTOX®

CONSTRUCTION PRODUCTS REGULATION
BS EN 50575
CLASS Cca
s2, d2, a1
INDEPENDENTLY VERIFIED

Construction

Conductor Material	: Bare Copper, Class 5
Insulation Material	: Low Smoke Halogen Free (LSHF)
Sheath Material	: Low Smoke Halogen Free (LSHF)
Sheath Colour	: White
Core Identification	: 2core – Brown, Blue 3core – Brown, Blue, Green/Yellow
	: 4core – Brown, Black, Grey, Green/Yellow
	: 5core – Brown, Black, Grey, Blue, Green/Yellow

Electrical Characteristics

Conductor Resistance	: BS EN 60228
Working Voltage	: 300/500V

Physical Characteristics

Bend Radius	: 6 x cable OD
Temperature Rating	: Flexing -5°C to +60°C

Standards

Manufactured to	: EN 50525-3-11
Flame Retardant	: EN 60332-1-2
Halogen Gas Emission	: EN 50267-2-1
Low Smoke Emission	: EN 61034-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Cca – s2, d2, a1 (EN50575:2014+A1:2016)

Part No.	Cores x mm²	Weight kg/km	OD mm
3180070204-C34	2 x 0.75	55	6.3
3180070304-C34	3 x 0.75	66	6.7
3180070404-C34	4 x 0.75	81	7.3
3180070504-C34	5 x 0.75	100	8.1
3180100204-C34	2 x 1.0	64	6.6
3180100304-C34	3 x 1.0	77	7.0
3180100404-C34	4 x 1.0	98	7.9
3180100504-C34	5 x 1.0	120	8.6
3180150204-C34	2 x 1.5	87	7.4
3180150304-C34	3 x 1.5	109	8.1
3180150404-C34	4 x 1.5	141	9.0
3180150504-C34	5 x 1.5	174	10.0

Part No.	Cores x mm²	Weight kg/km	OD mm
3180250204-C34	2 x 2.5	132	9.1
3180250304-C34	3 x 2.5	166	9.9
3180250404-C34	4 x 2.5	205	10.8
3180250504-C34	5 x 2.5	254	12.0
3180400304-C34	3 x 4.0	229	11.3
3180400404-C34	4 x 4.0	286	12.3
3180400504-C34	5 x 4.0	362	13.9

FS Cables Ltd
Export Sales
01727 840 841
+44 1727 849 841
sales@fscables.com
sales@fscglobal.com
www.fscables.com
www.fscglobal.com

Date: 12/08/2020
Revision: 1.1
Author: GB
Checked: GB

Information and images on this techincal datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.