

Description: Single Core Flexible Cable, Low Smoke Halogen Free (LSHF) Insulation. Conforming to H05Z-K & BS EN 50525-3-41

NILTOX®



Construction

Conductor Material : Bare Copper, Class 5
 Insulation Material : Low Smoke Halogen Free (LSHF)
 Insulation Colour : Replace XX on the end of the part number with the colour

00	Black	04	White	08	Orange
01	Blue	05	Grey	09	Yellow
02	Brown	06	Violet	10	Green
03	Red	07	Pink	99	Green/ Yellow

Electrical Characteristics

Nominal Conductor Resistance : BS EN 60228
 Voltage Rating : 300/500 V

Physical Characteristics

Overall Diameter : See Table
 Min. Bend Radius : 6 x OD
 Temperature Rating : -15°C to +90°C
 Weight : See Table

Standards

Flame Retardant : BS EN 60332-1-2
 Low Smoke Generation : BS EN 61034-2
 Halogen Gas Emission : BS EN 60754-1&2
 Manufactured in accordance to : BS EN 50525-3-41
 RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Dca s1, d0, a1 (EN50575:2014+A1:2016)

Part No.	Size mm ²	Weight kg/km	OD mm
249010XX-D19	1.0	16	2.8