

Description: Single Core Flexible Cable, Low Smoke Halogen Free (LSHF) Insulation. Conforming to H07Z-K & BS EN 50525-3-41

NILTOX®



Construction

Conductor Material : Bare Copper, Class 5
 Insulation Material : Low Smoke Halogen Free (LSHF)
 Insulation Colour : Replace XX on the end of the part number with the colour

00	Black	04	White	08	Orange
01	Blue	05	Grey	09	Yellow
02	Brown	06	Violet	10	Green
03	Red	07	Pink	99	Green/ Yellow

Electrical Characteristics

Nominal Conductor Resistance : BS EN 60228
 Voltage Rating : 450/750 V

Physical Characteristics

Overall Diameter : See Table
 Min. Bend Radius : 6 x OD
 Temperature Rating : -15°C to +90°C
 Weight : See Table

Standards

Flame Retardant : BS EN 60332-1-2
 Low Smoke Generation : BS EN 61034-2
 Halogen Gas Emission : BS EN 60754-1&2
 Manufactured in accordance to : BS EN 50525-3-41
 RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Dca s2, d2, a3 (EN50575:2014+A1:2016)

Part No.	Size mm ²	Weight kg/km	OD mm	Part No.	Size mm ²	Weight kg/km	OD mm
249015XX-D36	1.5	21	3.4	249500XX-D36	50	560	13.9
249025XX-D36	2.5	33	4.1	249700XX-D36	70	780	16.0
249040XX-D36	4.0	49	4.8	249950XX-D36	95	1000	18.2
249060XX-D36	6.0	70	5.3	249120XX-D36	120	1300	20.2
249100XX-D36	10	125	6.8	249150XX-D36	150	1600	22.5
249160XX-D36	16	180	8.1	249185XX-D36	185	2000	24.9
249250XX-D36	25	275	10.2	249240XX-D36	240	2600	28.4
249350XX-D36	35	380	11.7				