



# Profibus DP Marin SHF2

LSZH SHF2

Flexible Type A, 2x0,35 mm<sup>2</sup>

UV

DNV-GL, ABS




sales@fscglobal.com

## Application

Profibus data cable for communication systems and closed loop marine control systems.

## Construction

Conductor	Stranded Plain Cu AWG22 (0.35mm <sup>2</sup> )
Insulation	Foamskin PE 2.75 [mm]
No. of pairs	1
Screen	Al-polyester + Al tape
Screen 2	Tinned Cu braid 60 [% optical coverage]
Jacket	Black SHF2
O.D.	8.6 [mm]
Weight	95 [kg/km]
Jacket marking	NEK KABEL - PROFIBUS DP MARIN 1X0,35mm <sup>2</sup> SHF2- 100V-LSOH, DNV-GL, ABS



## Specifications

Operating temperature	-40 – +90 [°C]
Loop resistance screen-conductor	0.11 [[Ω/m]]
Loop Resistance / Inductance Ratio	<15 (nom. 8.5) [μH/Ω]
Inductance	0.9 [μH/m]
Characteristic impedance	@ 3-20 MHz: 150 ± 15Ω @ 38,4 kHz: 185±18,5Ω @ 9,6 kHz: 250 ± 25Ω
Conductor resistance	<55 [Ω/km]
Insulation resistance	≥ 1 [GΩ x km]
Test voltage	1000 [kV-DC 1 min.]
Capacitance	<30 (nom. 28) [pF/m] at 800 - 1000 Hz
Min. bending radius	20 [x outer diam]



## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1, -2
Sheathing material	IEC 60092-360 (359)
Flame retardant	IEC 60332-1
Toxic gases max.	EN 50305 9.2
Fire retardant	IEC 60332-3-22
Ozone resistant	DIN VDE 0472 part 805 B 1483
Smoke emission	IEC 61034-1, -2
Field bus specifications	IEC 61158-2 ed. 1
UV-resistant	ASTM G 154
Certification	DNV-GL, ABS
Part No.	1091038



This product is also available with MUD resistant jacket, Part.no. 1091039  
 or armoured, Part.no. 1087370  
 or armoured with MUD resistant jacket, Part.no. 1091035



## Attenuation nominal, max 105%

Frequency MHz	Attenuation dB/100m
16	<4.5
4	<2.2
0,038	<0.5
0.0096	<0.3

## Updated

Date	Rev.	Description
16.09.2016	1	ABS approved
19.01.2017	2	Additional technical data