



# RG 59 B/U Marine

75Ω  
SHF1  
DNV-GL, ABS



sales@fscglobal.com


## Application

Coaxial cable for data- and video, especially designed for ship- and offshore applications. Electrical data in compliance with MIL C - 17/F



## Construction

Conductor	Copperweld 0.58 ± 0.025 [mm]
Dielectricum	LDPE 3.7 ± 0.1 [mm]
Screen	Al-polyester-Al tape 100 [% optical coverage]
Screen	Cu-braid 93 [% optical coverage]
Jacket	Black SHF1
O.D.	6.2 ± 0.1 [mm]
Weight	53 [kg/km]
Jacket marking	NEK Kabel RG 59 B/U Marine, DD.MM.YY batch number and meter marked



## Specifications

Operating temperature	-30 – 70 [°C]
Characteristic impedance	75 ± 3 Ω
Braid Resistance	9 [Ω/km]
Conductor resistance	154 [Ω/km]
Test voltage	4.5 [kV]
Capacitance	67 [pF/m]
Min. bending radius	5 [x outer diam]
Min. bending radius flexible	10 [x outer diam]

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1, -2 NES 713
Design and testing standards	IEC 60096-0-1 Ed 3
Sheathing material	IEC 60092-360 (359)
Flame retardant	IEC 60332-1
Fire retardant	IEC 60332-3-22 Cat.A
Smoke emission	IEC 61034-1, -2
Certification	DNV-GL, ABS
Part No.	1092452





### Attenuation nominal, max 105%

Frequency MHz	Attenuation dB/100m
5	2.4
10	3.0
50	6.8
100	10.0
200	14.2
300	17.5
500	23.5
800	30.2
1000	34.2
1350	40.3
1500	43.4
1750	47.7
2250	55.0
2500	58.1
2750	61.3
3000	65.9

### Structural return loss

MHz	dB
30 – 300	>31
300 – 600	>28
600 – 1000	>24
1000 – 2000	>18
2000 – 3000	

### Screen effectiveness IEC 61196-1

MHz	dB
100 – 900	>90
900 – 2000	>80
2000 – 3000	>70