SY Multicore GSWB Colour Coded PVC
Technical Datasheet

Description: Multicore Signal & Control Cable with Galvanised Steel Wire Braid, Polyvinyl Chloride (PVC) Clear Sheath.

CONSTRUCTION PRODUCTS REGULATION
BS EN 50575
CLASS Eca
INDEPENDENTLY VERIFIED

Construction

Conductor Material	: Bare Copper, Class 5
Insulation Material	: Polyvinyl Chloride (PVC)
Bedding Material	: Polyvinyl Chloride (PVC)
Bedding Colour	: Grey
Overall Armour	: Galvanised Steel Wire Braid (≥ 75% Coverage)
Sheath Material	: Polyvinyl Chloride (PVC)
Sheath Colour	: Clear
Core Identification	: 2core – Brown, Blue 3core – Brown, Blue, Green/Yellow
	: 4core – Brown, Black, Grey, Green/Yellow
	: 5core – Brown, Black, Grey, Blue, Green/Yellow

Electrical Characteristics

Conductor Resistance	: BS EN 60228
Insulation Resistance	: 200 MΩ.M
Working Voltage	: 300/500V
Test Voltage (AC)	: 2000V

Physical Characteristics

Bend Radius	: Flexing 10 x OD
	Static 7.5 x OD
Temperature Rating	: Flexing -5°C to +70°C
	Static -20°C to +70°C

Standards

Flame Retardant	: BS EN 60332-1-2
RoHS3 Compliant	: Yes
CE Compliant	: LVD (2014/35/EU), CPR (305/2011)
CPR Classification	: Eca (EN50575:2014+A1:2016)

Part No.	Cores x mm²	Weight kg/km	OD mm
11000502C-E00	2 x 0.5	77	7.6
11000503C-E00	3 x 0.5	101	8.0
11000504E-E00	4 x 0.5	116	9.1
11000505E-E00	5 x 0.5	127	9.4
11000702C-E00	2 x 0.75	95	8.0
11000703C-E00	3 x 0.75	105	8.3
11000704E-E00	4 x 0.75	136	9.3
11000705E-E00	5 x 0.75	172	9.8
11001002C-E00	2 x 1	124	8.2
11001003C-E00	3 x 1	139	8.5
11001004E-E00	4 x 1	150	9.5
11001005E-E00	5 x 1	190	10.1
11001502C-E00	2 x 1.5	153	8.8
11001503C-E00	3 x 1.5	162	9.6
11001504E-E00	4 x 1.5	193	10.4
11001505E-E00	5 x 1.5	234	11.1

Part No.	Cores x mm²	Weight kg/km	OD mm
11002502C-E00	2 x 2.5	192	10.5
11002503C-E00	3 x 2.5	237	11.0
11002504E-E00	4 x 2.5	297	12.6
11002505E-E00	5 x 2.5	365	13.6
11004003C-E00	3 x 4.0	353	13.4
11004004C-E00	4 x 4.0	458	14.8
11004005E-E00	5 x 4.0	556	16.1
11006003C-E00	3 x 6.0	451	14.9
11006004E-E00	4 x 6.0	570	16.7
11006005E-E00	5 x 6.0	693	18.1
11010003C-E00	3 x 10	744	19.7
11010004E-E00	4 x 10	906	21.2
11010005E-E00	5 x 10	1077	24.5
11016003C-E00	3 x 16	1108	22.7
11016004E-E00	4 x 16	1406	27.9
11016005E-E00	5 x 16	1780	31.1

Part No.	Cores x mm²	Weight kg/km	OD mm
11025004E-E00	4 x 25	205	33.8
11025005E-E00	5 x 25	2529	37.3
11035004E-E00	4 x 35	2571	36.7
11035005E-E00	5 x 35	3268	41.1
11050004E-E00	4 x 50	3613	39.9
11050005E-E00	5 x 50	4367	44.3
11070004E-E00	4 x 70	4893	45.6
11070005E-E00	5 x 70	5869	51.7
11095004E-E00	4 x 95	6423	50.2
11095005E-E00	5 x 95	8162	56.9
11120004E-E00	4 x 120	8235	56.1
11150004E-E00	5 x 150	10324	63.2

FS Cables Ltd
Export Sales

01727 840 841
+44 1727 849 841

sales@fscables.com
sales@fscglobal.com

www.fscables.com
www.fscglobal.com

Date: 27/02/2020
Revision: 1.0
Author: GB Checked: GB

Information and images on this techincal datasheet are intended for guidance only and products may vary due to manufacturing changes, technical improvements and commercial factors. We reserve the right to amend the product information without notice or liability.