


Part No.: TSS162C-F00
Description: TruSound 16awg two core speaker cable with a PE outer sheath and a water blocking tape. The cable also has oxygen free bare copper conductors.

Construction

Conductor Material : 99.999% Oxygen Free Bare Copper
 Number of Strands : 41/0.2mm
 Insulation Material : Polyvinylchloride (PVC)
 Number of Cores : 2
 Overall Tape : Water Blocking Fleece
 Sheath Material : Polyethylene (PE)
 Sheath Colour : Black
 Core Identification : Red, Black



Electrical Characteristics

Nominal Conductor Resistance : < 13.7 Ω /km
 Insulation Resistance : > 200 M Ω .M
 Voltage Rating : 450/750V *Applies to CE marked FSC/Tru branded stock only*
 Test Voltage : 2.5kV for 5 Minutes

Physical Characteristics

Overall Diameter : 6.5 \pm 0.2mm
 Min. Bend Radius : 10 x OD
 Temperature Rating : 0°C to +70°C
 Weight : 40 kg/km

Standards

RoHS3 Compliant : Yes
 UV & Weather Resistant : ISO 4892-3
 CE Compliant : LVD (2014/35/EU), CPR (305/2011)
 CPR Classification : Fca (EN50575:2014+A1:2016)